

[54] STACKED-PLATE HEAT EXCHANGER

[76] Inventor: Dieter C. Steeb, Im Schönenbühl,
CH-9050 Steinegg-Appenzell,
Switzerland

[21] Appl. No.: 347,068

[22] Filed: Feb. 8, 1982

[30] Foreign Application Priority Data

Feb. 25, 1981 [DE] Fed. Rep. of Germany 3107010

[51] Int. Cl.³ F28D 9/02; F28F 3/06

[52] U.S. Cl. 165/153; 165/166;
165/183; 165/DIG. 9

[58] Field of Search 165/167, 166, 165, 170,
165/183, 185, 149, 152, 153, DIG. 9

[56] References Cited

U.S. PATENT DOCUMENTS

902,812	11/1908	Goetz et al.	165/170
1,404,721	1/1922	Stein	165/165
3,205,563	9/1965	Pauls et al.	29/157.3 V
3,650,005	3/1972	Kamiya et al.	165/170 X
3,932,090	1/1976	Brumlik	425/381
4,083,400	4/1978	Dziedzic et al.	165/165
4,150,719	4/1979	Thielen et al.	165/166 X

FOREIGN PATENT DOCUMENTS

2332047	1/1975	Fed. Rep. of Germany	165/166
2259006	7/1976	Fed. Rep. of Germany	.
7835175	2/1979	Fed. Rep. of Germany	.
3011011	9/1980	Fed. Rep. of Germany	165/166
2093583	9/1982	United Kingdom	165/166

Primary Examiner—Sheldon J. Richter

Attorney, Agent, or Firm—Hopgood, Calimafde, Kalil,
Blaustein & Judlowe

[57] ABSTRACT

A heat exchanger comprises a stack of spaced plates such that elongate plane-parallel fluid-conduit systems are established between adjacent pairs of plates, the plane-parallel conduit systems being in two sets, with the conduit system of one set being interposed between two conduit systems of the other set. Between adjacent plates, a conduit system is closed along its two laterally opposite edges, by rail-like spacers between the involved adjacent plates. The conduit system of at least one set comprises corrugated structures taking the form of extruded sections and having ridges which are connected to the lateral-edge closures of the involved conduit system.

7 Claims, 2 Drawing Figures

